

### **COMMERCIAL OUTDOOR LED SCREEN**

3D Billboard Advertising LED Screen Commercial Advertising Billboard P2.5 P3 P4 P5 P6 P8 P10 Outdoor LED Display

Pixel Pitch: 2.5/3/4/5/6/6.67/8/10/16mm

Cabinet Size: Customized

Operating Environment: Outdoor





## Outdoor Commercial Advertising LED Display





#### Outdoor Fixed 3D LED Screen

### **Product Description**



#### Outdoor fixed led screen

Certainly the best option for outdoor advertising, this Fixed LED display carries some features that make it highly suitable for outdoor areas. It can work in different brightness level and outdoor circumstances. Fixed LED display can also be used at stage, bank, promotion, exhibition, station, KTV, stadium, airport and other outdoor places.



#### Unique Cabinet Design - Easy to Install & Transport

The cabinet of outdoor LED Screen features unique rugged design which makes it easy to carry and install. The lightweight cabinet is easy to carry and saves transportation cost. It's damage free and lasts for a lifetime.



#### Get Every Detail in Picture

We spend some time with every detail of the product, so that you can enjoy every detail of your marketing pictures. The pixel-perfect pictures are a treat to watch. It means, you will not miss any detail in the picture, video or text displayed on the screen.







#### High IP Rating IP65 - Safe and Reliable


The special waterproof design of LED Screen protects it from water and dust. When installed in outdoor areas, protection is a serious matter. Special guard protects it from environment dangers. High IP Rating IP65 ensures great quality outputs in every condition.





# Installation of outdoor led display


















## **Control system Connection**



Multi -media equipment



Style	JF2.5	JF3	JF3.076	JF4	JF5	JF6	JF6.6		
Pixel Pitch(mm)	2.5	3	3.076	4	5	6	6.67		
Pixel Matrix Per Sq.m	160000	111111	105688	62500	40000	27777	22500		
Pixel Configuratio n	SMD1415	SMD1921	SMD1415	SMD1921	SMD2525	SMD3535	SMD2727		
Brightness (nits)	5000	5000	5000	5000-5500	5000-6000	5500-6000	5500-6000		
Scan	1/16	1/16	1/13	1/10	1/8	1/8	1/6		
Module Dimension	320x160m m	192x192m m	320x160m m	320x160m m	320x160m m	192x192m m	320x160m m		
Cabinet Dimension	960x960mm (Cabinet size can be customized according to module size)								
Cabinet Weight	42kg / 93lb (Iron)	42kg / 93lb (Iron)	41kg / 90lb (Iron)	40kg / 88lb (Iron)	40kg / 88lb (Iron)	46kg / 101lb (Iron)	46kg / 101lb (Iron)		
Power Con. (Max / Avg)	900/ 180 w/sq.m	900/ 180 w/sq.m	900/ 180 w/sq.m	900/ 180 w/sq.m	900/ 180 w/sq.m	900/ 180 w/sq.m	900/ 180 w/sq.m		
IP Rate	IP65								
Service Access	Rear								
Refresh Rate (HZ)	1920-3840HZ								
Grey Scale (bit)	16bit								
Viewing Angle (H/V)	160/140								



Input Voltage (AC)	110V/2
Style	J

240V

Voltage (AC)							
Style	JF8	JF10	JF10S	JF16			
Pixel Pitch(mm)	8	10	10.00	16.00			
Pixel Matrix Per Sq.m	15625	10000	10000	10000			
Pixel Configuration	SMD3535	SMD3535	SMD3535	DIP346			
Brightness (nits)	5500-6500	5500-6500	6500-7000	8500			
Scan	1/5	1/4	1/2	1/1			
Module Dimension	320x160mm	320x160mm	320x160mm	256x256mm			
Cabinet Dimension	960x960mm (C	abinet size can be	changed accordin	g to module size)			
Cabinet Weight	42kg / 93lb (Iron)	42kg / 93lb (Iron)	41kg / 90lb (Iron)	40kg / 88lb (Iron)			
Power Con. (Max / Avg)900/ 180 w/sq.m 900/ 180 w/sq.m 900/ 180 w/sq.m 900/ 180 w/sq.m							
IP Rate	IP65						
Service Access	Rear						
Refresh Rate (HZ)	1920-3840HZ						
Grey Scale (bit)	16bit						
Viewing Angle (H/V)	160/140						
Input Voltage (AC)	110V/240V						